

DHI-NVR4208/4216/4232-4KS2

8/16/32 Channel 1U 4K&H.265 Lite Network Video Recorder



- · H.265/H.264 codec decoding
- · Max 200Mbps Incoming Bandwidth
- Up to 8MP Resolution for Preview and Playback
- · Up to 2ch@4K/8ch@1080P decoding
- HDMI/VGA simultaneous video output













System Overview

Dahua NVR4000-4KS2 is introduced as the first Lite series NVR that supports for 4K and H.265 encoding technology with excellent performance at an affordable price. For applications where image details are highly required, it delivers the capability of 4K resolution processing. The NVR can be served as edge storage, central storage or backup storage with an intuitive shortcut operation menu for remote management and control.

Due to its cost-effective and easy-to-install design, this NVR is ideal for a wide range of applications such as public safety, water conservancy, transportation, city centers, education, and financial institutions.

The NVR is compatible with numerous third-party devices making it the perfect solution for surveillance systems that work independently of video management system (VMS). It features an open architecture that supports for multi-user access and is compatible with ONVIF 2.4 protocol, enabling interoperability with IP cameras.

Functions

4K Resolution

4K resolution is a revolutionary breakthrough in image processing technology. 4K delivers four times the resolution of standard HDTV 1080p cameras and offers superior picture quality and image details. 4K resolution improves the clarity of a magnified scene to view or record crisp forensic video from large areas.

High Efficiency Video Coding (H.265)

The H.265 (ITU-T VCEG) video compression standard offers double the data compression ratio at the same level of video quality, or substantially improved video quality at the same bit rate, as compared to older video compression technologies. H.265 offers such impressive compression by expanding the pattern comparison and difference-coding, improving motion vector prediction and motion region merging, and incorporating an additional filtering step called sample-adaptive offset filtering.

Intelligent Video System

Working with IVS-enabled IP cameras, the NVR recognizes and records video that contains IVS data on all IP channels. The NVR records standard intelligence at-the-edge features, as well as premium IVS features that detect abandoned or missing objects, Tripwire violations, and intrusion violations. The NVR is also capable of recording business analysis data — Facial Detection, People Counting, and Heat Map — from IP cameras with built-in Intelligent Business Analytics.

ANR (Automatic Network Replenishment Technology)

Network Video Recorders with the ANR function automatically store video data on an IP camera SD card when the network is disconnected. After recovery of the network, the NVR automatically retrieves the video data stored on the camera.

Easy4ip

The Easy4ip app is available on the iOS App Store and Google Play. It makes surveillance easy and simple, allowing you to remotely access NVR devices, view live video, receive event push notifications, and search for recorded videos from an iPhone, iPad, or Android phone at anytime from virtually anywhere!



Technical Specification		Third-party Support	
System		Third-party Support	Arecont Vision, Airlive, AXIS, Canon, Dynacolor, JVC, LG, Panasonic, Pelco, PSIA, Samsung, Sany Sony, Watchnet and more
Main Processor Operating System	Quad-core embedded processor Embedded LINUX	Network	
	Ellipedaca Elivox		1.0.1.0.0.0.1.1.1.1.1.1.1.1.1.1.1.1.1.1
Aduio and Video		Interface	1 RJ-45 Port (10/100/1000Mbps)
IP Camera Input	8/16/32 Channel	Ethernet Port	1 Independent 1000Mbps Ethernet Port
Two-way Talk	1 Channel Input, 1 Channel Output, RCA	PoE	N/A
Display			HTTP, HTTPS, TCP/IP, IPv4/IPv6, UPnP, RTSP, UDSMTP, NTP, DHCP, DNS, IP Filter, PPPoE, DDNS, I
Interface	1 HDMI, 1 VGA	SNMP, IP Search (Support Dahua IP came	SNMP, IP Search (Support Dahua IP camera, DV NVS, etc.), Easy4ip
Resolution	HDMI: 3840×2160, 1920×1080, 1280×1024, 1280×720	Max. User Access	128 users
Nesolution	VGA: 1920×1080, 1280×1024, 1280×720	Smart Phone	iPhone, iPad, Android
Decoding Capacity	2ch@4K 30fps, 8ch@1080P 30fps	Interoperability	ONVIF 2.4, SDK, CGI
	8CH: 1/4/8/9	Storage	
Multi-screen Display	16CH: 1/4/8/9/16	Internal HDD	2 SATA III Ports, Up to 6 TB capacity for each HI
	32CH: 1/4/8/9/16/25/36	HDD Mode	Single
OSD	Camera title, Time, Camera lock, Motion detection, Recording	Auxiliary Interface	
Recording		USB	2 ports(1 USB2.0, 1 USB3.0)
Compression	H.265/ H.264		
Resolution	8Mp/ 6Mp/ 5MP/ 4MP/ 3MP/ 1080P/ 1.3MP/ 720P etc.	RS232	N/A
Record Rate	200Mbps	RS485	N/A
Bit Rate	16Kbps ~ 20Mbps Per Channel	Electrical	
Record Mode	Manual, Schedule (Regular, Continuous), MD (Video detection: Motion Detection, Tampering, Video Loss), Stop	Power Supply	DC12V/4A
Record Interval	1~120 min (default: 60 min), Pre-record:	Power Consumption	< 6.9W(without HDD)
	1~30 sec, Post-record: 10~300 sec	Environmental	
Video Detection and Alarm		Operating Conditions	-10°C ~ +55°C (+14°F ~ +131°F), 86 ~ 106kpa
Trigger Events	Recording, PTZ, Tour, Video Push, Email, Snapshot, Buzzer and Screen Tips	Storage Conditions	-20°C ~ +70°C (-4°F ~ +158°F), 0 ~ 90% RH
Video Detection	Motion Detection, MD Zones: 396 (22 × 18), Video Loss and Tampering	Construction	1U, 375mm×281.5mm×56mm
Alarm input	4 Channel		(14.8" x 11.1" x2.2")
Relay Output	2 Channel	Net Weight	1.6kg (3.5 lb) (without HDD)
Playback and Backup		Gross Weight	3.2kg(7.1 lb)(without HDD)
Playback	8CH: 1/4/9	Certifications	
	16/32CH: 1/4/9/16	CE	EN55032, EN55024, EN50130-4, EN60950-1
Search Mode	Time /Date, MD and Exact Search	FCC	Part 15 Subpart B, ANSI C63.4-2014
Playback Function	(accurate to second), Smart search Play, Pause, Stop, Rewind, Fast play, Slow Play, Next File, Previous File, Next Camera, Previous Camera, Full Screen, Backup Selection, Digital Zoom	UL	UL60950-1
Backup Mode	USB Device/Network		

Lite Series | DHI-NVR4208/4216/4232-4KS2

Ordering Information				
Туре	Part Number	Description		
8 Channel NVR	DHI-NVR4208-4KS2	8 Channel 1U 4K&H.265 Lite Network Video Recorder		
16 Channel NVR	DHI-NVR4216-4KS2	16 Channel 1U 4K&H.265 Lite Network Video Recorder		
32 Channle NVR	DHI-NVR4232-4KS2	32 Channle 1U 4K&H.265 Lite Network Video Record		
Accessories	N/A	N/A		



Dimensions (mm)



