

## 9-Port PoE Switch with 8 PoE Ports 15.4W (POE31008P)

### 9-Port PoE Switch with 8 PoE Ports 15.4W



- ◆ Can supply power to network surveillance cameras that without PoE function
- ◆ 9x 10/100Mbps auto-sensing RJ45 ports, 8x 10/100Mbps PoE ports, 1x uplink port
- ◆ Supports port auto-flip (Auto MDI/ MDIX)
- ◆ External power supply
- ◆ Maximum PoE ports power: 120W (Port 1 to Port 8)
- ◆ Maximum power of single PoE port: 15.4W
- ◆ Adopts store-and-forward architecture
- ◆ IEEE 802.3af power on up to 8 ports
- ◆ Features with fanless, natural cooling, small, compact and quiet design, suitable for desktop or wall
- ◆ Built-in 1U rack power supply series, easy to place it into standard mounting brackets

### Product Description

This **POE31008P** switch provides a network point for power supply and data transmission. All the 9 Ethernet ports can be connected with 10/100Mbps quickly, and the uplink port is Ethernet interface, among which 1-8 ports can provide standard IEEE 802.3af power supply. Due the advanced self-sensing algorithm supply power for IEEE802af terminal unit only, there is no need to worry about damaging proprietary PoE or non-PoE standard equipment. In addition, it will stop power supply when PoE devices are not connected. In short, The **POE31008P** features simple and reliable design, automatic identification PoE requirements, duplex and high-speed.


This cost-effective **POE31008P** provide network layout need to simplify wireless access point (AP) and IP-based surveillance cameras network cameras in order to install in commercial network and home network. The devices far away from power socket are very suitable for hanging on the wall or ceiling. PoE eliminates the need for connecting these devices to power socket. So it make more flexible for those difficult to connect with AC power socket, and cut down the installation cost. It is ideal choice for those want to deploy a small commercial network and home network that use wireless access point (AP) and IP-based surveillance cameras.

Technical Specification

|  |   |
|--|---|
| <b>Product Name</b>                    | 9-Port PoE Switch with 8 PoE Ports 15.4W  |
| <b>Product Model</b>                   | <b>POE31008P</b>  |
| <b>Connector</b>                       | 9x 10/100M copper cable RJ45 ports(all ports support MDI/MDIX)<br>8x PoE ports, 1x uplink port  |
| <b>Transfer Mode</b>                   | Store-And-Forward   |
| <b>Network Medium</b>                  | 10BASE-T: Cat3,4,5 UTP(≤100 meter)<br>100BASE-TX: Cat5 or more UTP (≤100 meter)<br>Data transmission distance: 100m   |
| <b>Performance Specifications</b>      | Bandwidth: 1.6Gbps (non-blocking)<br>Network Latency (100 to 100M bps): maximum delay less than 20 microseconds<br>Packet Buffer Memory: 96KB<br>Address Database Size: 1,000<br>MTBF: 190,000 hours (about 21 years) |
| <b>Network Protocols and Standards</b> | IEEE 802.3i 10BASET<br>IEEE 802.3u 100BASETX<br>IEEE 802.3x Flow Control<br>IEEE 802.1af DTE Power via MDI<br>IEEE 802.3af  |
| <b>LEDs Status</b>                     | System: power supply<br>Every Port: connecting, PoE working status  |
| <b>Power</b>                           | Maximum PoE power: 120W<br>PoE port power:15.4 W(1~8 port)<br>Power input: AC100-240V 50/60Hz; (every country use a custom power plug)  |
| <b>Dimensions/Weight</b>               | Dimensions(LxWxH): 195x110x35mm, 0.493kg  |
| <b>Working Environment</b>             | Operating Temperature: -20 ° ~ 55 ° C<br>Storage Temperature: -20 ° ~ 75 ° C<br>Operating Humidity: 10% ~ 95%, non-condensing   |
| <b>Radiation</b>                       | CE mark, commercial<br>FCC Part 15 Class B<br>VCCI Class B<br>EN 55022 (CISPR 22), Class B  |
| <b>Safety</b>                          | CE Mark ,commercial<br>CE/LVD EN60950, RoHS   |
| <b>Warranty</b>                        | 1 year warranty(2 yeas warranty for power adapter)  |


## 9-Port PoE Switch with 8 PoE Ports 15.4W

### Product Size Display



- A. 8x PoE Power Port
- B. Uplink Port
- C. DC 48V Input

### Product Usage Display



## 9-Port PoE Switch with 8 PoE Ports 15.4W

---

### Product Ordering Information

---

**Product Model: POE31008P**

**Product Description:** 9x 10/100M Ethernet ports with 8x PoE ports and 1x uplink port, and 1-8 ports supports IEEE802.3af POE international standard, each port power is 15.4W, total power is 120W

**Ordering Notes:** PoE default power supply is end-span (1/2, 3/6 line pair), alternative PoE Power supply is mid-span (4/5, 7/8 line pair)

### Product Packing Lists

---

|                      |                                     |
|----------------------|-------------------------------------|
| <b>Packing Lists</b> | 9-Port PoE Switch 15.4W (POE31008P) |
|                      | Power Adapter                       |
|                      | User Guide                          |
|                      | Warranty Card                       |