

## HBL400

### Multi-Biometric Wi-Fi Smart Digital Lock



3D Structured Light Facial Recognition



Auto Opening and Closing



Remote Control



Fingerprint



Random Passcode



Doorbell



### Introduction

HBL400 is designed as a multi-biometric automatic video smart lock. It could unlock and lock itself. It is compatible with USmart Go, an application designed for home automation. Users could enjoy remote control and online real-time monitoring when connecting the smart lock to the Wi-Fi network.

What's more, HBL400 is an intelligent door lock powered by 3D Structured Light facial recognition technology, offering more accurate performance than infrared and visible light facial recognition technology. It works well during daylight and low-light environments. When the house owner returns, the lock will quickly extract their face data, then instantly calculate and compare the acquired information with the template stored in the smart lock. If the data matches, the smart lock will unlock automatically.


### Scenarios



Automatic locking and unlocking after verification



Real-time monitoring from the indoor



When someone presses the doorbell outside, the owner could take a look at the person through the app



Remotely unlock using the app

## Features

- Auto opening and closing according to personalization settings
- An OLED screen for monitoring the outdoor situation inside the house
- Compatible with USmart Go; remote control and real-time monitoring online through Wi-Fi
- 3D structured light facial recognition, quick verification and quick unlock
- A hidden fingerprint semi-conductor installed behind the outdoor handle unit with ergonomics and anti-collision design
- No need to deploy an additional doorbell
- Class C cylinder protection; even the outdoor unit of the lock is damaged, your home is still safe

## Specifications

<b>Material</b>	Aluminum Alloy and Tempered Glass
<b>Capacity</b>	IC S50 Card: 50 Face: 50 Fingerprint: 100 Password: 50 Administrator: 5
<b>Power Supply</b>	4,200mA; lithium battery
<b>Emergency Interface</b>	Micro USB 5V
<b>Mortise Type</b>	Chinese standard mortise (6068)
<b>MCBF</b>	>100,000
<b>Communication</b>	Wi-Fi
<b>Static Current</b>	<80uA
<b>Working Temperature</b>	-25°C to 75°C
<b>Working Humidity</b>	20% RH to 90% RH
<b>Induction Distance</b>	50cm to 100cm
<b>Recognition Speed</b>	1.25 seconds
<b>Random Password</b>	Supports
<b>Doorbell</b>	Supports
<b>Retrieving Unlocking Records Online</b>	Supports
<b>Application</b>	Duplexes, townhouses, apartments, condos, and other residential areas
<b>Door Thickness (mm)</b>	45 to 60 (customizable)
<b>Dimensions (mm)</b>	Outdoor unit: 400*74*23 Indoor unit: 400*74*24

## Dimensions (mm)

