

## DS-2CD2H55FWD-IZS

### 5 MP IR Vari-focal Turret Network Camera



#### Key Features

- 1/2.9" Progressive Scan CMOS
- 2944 × 1656 @20fps
- H.265, H.265+
- 120dB WDR
- IP67, IK10
- IR range: up to 30 m
- BLC/3D DNR/ROI/HLC
- Smart encoding: Support low bit rate
- 4 behavior analyses and face detection
- Color: 0.01 Lux @ (F1.2, AGC ON), 0 Lux with IR  
Color: 0.014 Lux @ (F1.4, AGC ON), 0 Lux with IR



## Specifications


<b>Camera</b>	
Image Sensor	1/2.9" Progressive Scan CMOS
Min. Illumination	Color: 0.01 Lux @ (F1.2, AGC ON), 0 Lux with IR Color: 0.014 Lux @ (F1.4, AGC ON), 0 Lux with IR
Shutter Speed	1/3 s to 1/100,000 s
Slow Shutter	Yes
Day & Night	IR Cut Filter
Digital Noise Reduction	3D DNR
WDR	120dB
3-Axis Adjustment	Pan: 0° to 355°, tilt: 0° to 75°, rotate: 0° to 360°
<b>Lens</b>	
Focal length	2.8 to 12 mm
Aperture	F1.4
Focus	Auto
FOV	Horizontal field of view: 88° to 27° Vertical field of view: 48° to 16° Diagonal field of view: 104° to 32°
Lens Mount	Φ14
<b>IR</b>	
IR Range	Up to 30 m
Wavelength	850nm
<b>Compression Standard</b>	
Video Compression	Main stream: H.265/H.264 Sub stream: H.265/H.264/MJPEG Third stream: H.265/H.264
H.264 Type	Main Profile/High Profile
H.264+	Main stream supports
H.265 Type	Main Profile
H.265+	Main stream supports
Video Bit Rate	32 Kbps to 16 Mbps
Audio Compression	G.711/G.722.1/G.726/MP2L2/PCM
Audio Bit Rate	64Kbps(G.711)/16Kbps(G.722.1)/16Kbps(G.726)/32-192Kbps(MP2L2)
<b>Smart Feature-set</b>	
Behavior Analysis	Line crossing detection, intrusion detection, unattended baggage detection, object removal detection
Exception Detection	Scene change detection
Face Detection	Yes
Region of Interest	Support 1 fixed region for main stream and sub stream
<b>Image</b>	
Max. Resolution	2944 × 1656
Main Stream	50Hz: 20 fps (2944 × 1656), 25 fps (2560 × 1440, 1920 × 1080, 1280 × 720) 60Hz: 20 fps (2944 × 1656), 30 fps (2560 × 1440, 1920 × 1080, 1280 × 720)
Sub Stream	50Hz: 25fps (640 × 480, 640 × 360, 320 × 240) 60Hz: 30fps (640 × 480, 640 × 360, 320 × 240)

Third Stream	50Hz: 25fps (1280 × 720, 640 × 360, 352 × 288) 60Hz: 30fps (1280 × 720, 640 × 360, 352 × 240)
Image Enhancement	BLC/3D DNR/HLC
Image Setting	Rotate mode, saturation, brightness, contrast, sharpness adjustable by client software or web browser
Day/Night Switch	Day/Night/Auto/Schedule/Triggered by Alarm In
*Note: When the main stream resolution is 2944 × 1656, max frame rate is 20 fps for all streams.	
<b>Network</b>	
Network Storage	Support Micro SD/SDHC/SDXC card (128G), local storage and NAS (NFS,SMB/CIFS), ANR
Alarm Trigger	Motion detection, video tampering, network disconnected, IP address conflict, illegal login, HDD full, HDD error, Alarm input, Alarm output
Protocols	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, Bonjour
General Function	One-key reset, anti-flicker, three streams, heartbeat, password protection, privacy mask, watermark, IP address filter
Firmware Version	V5.5.52
API	ONVIF (PROFILE S, PROFILE G), ISAPI
Simultaneous Live View	Up to 6 channels
User/Host	Up to 32 users 3 levels: Administrator, Operator and User
Client	iVMS-4200, Hik-Connect, iVMS-5200, iVMS-4500
Web Browser	IE8+, Chrome 31.0-44, Firefox 30.0-51, Safari 8.0+
<b>Interface</b>	
Audio	1 input (line in, 3.5 mm), 1 output(3.5 mm), mono sound
Communication Interface	1 RJ45 10M/100M self-adaptive Ethernet port
Alarm	1 input, 1 output (max. 12 VDC, 30 mA)
Video Output	No
On-board storage	Built-in Micro SD/SDHC/SDXC slot, up to 128 GB
SVC	Support H.264 and H.265 encoding
Reset Button	Yes
<b>Audio</b>	
Environment Noise Filtering	Yes
Audio Sampling Rate	8kHz/16kHz/32kHz/44.1kHz/48kHz
<b>General</b>	
Operating Conditions	-30 °C to +60 °C (-22 °F to +140 °F), Humidity 95% or less (non-condensing)
Power Supply	12 VDC ± 25%, PoE (802.3af) Terminal block for DC input
Power Consumption and Current	12 VDC, 0.92A, max. 11W PoE (802.3af, 36V to 57V), 0.35A to 0.22A, max. 12.5W
Protection Level	IP67, IK10
Material	Metal
Dimensions	Φ 135.8 mm × 145.5 mm (Φ 5.35" × 5.73")
Weight	With Package: Approx. 1220 g (2.69 lb.) Camera: Approx. 1060 g (2.34 lb.)

**Available Model:**

DS-2CD2H55FWD-IZS

**Dimensions**



**Accessories**



- |  |  |  |  |                                       |  |
|--|--|--|--|---------------------------------------|--|
| <p>DS-1473ZJ-135<br/>Distributed by<br/>Wall Mount</p> | <p>DS-1471ZJ-135<br/>Pendant Mount</p> | <p>DS-1281ZJ-DM23<br/>Inclined Ceiling<br/>Mount</p> | <p>DS-1475ZJ-SUS<br/>Vertical Pole<br/>Mount</p> | <p>DS-1476ZJ-SUS<br/>Corner Mount</p> | <p>DS-1473ZJ-135B<br/>Wall Mount<br/>with Junction Box</p> |
|--|--|--|--|---------------------------------------|--|

**Headquarters**

No.555 Qianmo Road, Binjiang District,  
Hangzhou 310051, China  
T +86-571-8807-5998  
overseasbusiness@hikvision.com

- |   |   |  |  |  |
|---|---|--|--|--|
| <p><b>Hikvision USA</b><br/>T +1-909-895-0400<br/>sales.usa@hikvision.com</p>         | <p><b>Hikvision Europe</b><br/>T +31-23-5542770<br/>sales.eu@hikvision.com</p>          | <p><b>Hikvision UK &amp; Ireland</b><br/>T +01628-902140<br/>sales.uk@hikvision.com</p>      | <p><b>Hikvision UAE</b><br/>T +971-4-4432090<br/>salesme@hikvision.com</p>       | <p><b>Hikvision Russia</b><br/>T +7-495-669-67-99<br/>saleru@hikvision.com</p>           |
| <p><b>Hikvision Australia</b><br/>T +61-2-8599-4233<br/>salesau@hikvision.com</p>     | <p><b>Hikvision Italy</b><br/>T +39-0438-6902<br/>info.it@hikvision.com</p>             | <p><b>Hikvision South Africa</b><br/>Tel: +27 (10) 0351172<br/>sale.africa@hikvision.com</p> | <p><b>Hikvision Singapore</b><br/>T +65-6684-4718<br/>sg@hikvision.com</p>       | <p><b>Hikvision Korea</b><br/>T +82-(0)31-731-8817<br/>sales.korea@hikvision.com</p>     |
| <p><b>Hikvision India</b><br/>T +91-22-28469900<br/>sales@pramahikvision.com</p>      | <p><b>Hikvision Brazil</b><br/>T +55 11 3318-0050<br/>Latam.support@hikvision.com</p>   | <p><b>Hikvision France</b><br/>T +33(0)1-85-330-450<br/>info.fr@hikvision.com</p>            | <p><b>Hikvision Spain</b><br/>T +34-91-737-16-55<br/>info.es@hikvision.com</p>   | <p><b>Hikvision Poland</b><br/>T +48-22-460-01-50<br/>info.pl@hikvision.com</p>          |
| <p><b>Hikvision Canada</b><br/>T +1-866-200-6690<br/>sales.canada@hikvision.com</p>   | <p><b>Hikvision Turkey</b><br/>T +90 (216)521 7070- 7074<br/>sales.tr@hikvision.com</p> | <p><b>Hikvision Kazakhstan</b><br/>T +7-727-9730667<br/>nikia.panfilov@hikvision.ru</p>      | <p><b>Hikvision Tashkent</b><br/>T +99-87-1238-9438<br/>uzb@hikvision.ru</p>     | <p><b>Hikvision Indonesia</b><br/>T +62-21-2933759<br/>Sales.Indonesia@hikvision.com</p> |
| <p><b>Hikvision Thailand</b><br/>T +662-275-9949<br/>sales.thailand@hikvision.com</p> | <p><b>Hikvision Malaysia</b><br/>T +601-7652-2413<br/>sales.my@hikvision.com</p>        | <p><b>Hikvision Vietnam</b><br/>T +84-974270888<br/>sales.vt@hikvision.com</p>               | <p><b>Hikvision Hong Kong</b><br/>T +852-2151-1761<br/>info.hk@hikvision.com</p> | <p><b>Hikvision Colombia</b><br/>sales.colombia@hikvision.com</p>                        |